

## FLASH INVERTER (FTKQ – Series)

Nama		Set	STKQ15SV	STKQ20SV	STKQ25SV
Model		Indoor	FTKQ15SVM4	FTKQ20SVM4	FTKQ25SVM4
		Outdoor	RKQ15SVM4	RKQ20SVM4	RKQ25SVM4
Kapasitas (Min~Max)		PK	0.50	0.75	1
		Btu/h	5,100 (2,400 ~ 6,500)	6,800 (3,400 ~ 8,200)	9,000 (3,400 ~ 9,900)
		kW	1.5 (0.7 ~ 1.9)	2.0 (1.0 ~ 2.4)	2.65 (1.0 ~ 2.9)
Daya Listrik (Min~Max)		W	310 (130 ~ 580)	510 (220 ~ 650)	810 (220 ~ 990)
COP (Min~Max)		W/W	4.84	3.92	3.27
Tingkat Tekanan Suara (H/L/SL)		Indoor	36/27/23	36/27/23	36/27/23
		Outdoor	49	49	49
Indoor Unit	Dimensi (HxWxD)	mm	285 × 770 × 223	285 × 770 × 223	285 × 770 × 223
	Berat Mesin	kg	8	8	8
Outdoor	Dimensi (HxWxD)	mm	418 x 695 x 244	418 x 695 x 244	418 x 695 x 244
	Berat Mesin	kg	21	21	21
Ukuran Pipa		Cair	inch	1/4	1/4
		Gas	inch	3/8	3/8
Maksimal Pipa		Panjang	m	15	15
		Tinggi	m	12	12

Nama		Set	STKQ35SV	STKQ50SV	STKQ60SV
Model		Indoor	FTKQ35SVM4	FTKQ50SVM4	FTKQ60SVM4
		Outdoor	RKQ35SVM4	RKQ50SVM4	RKQ60SVM4
Kapasitas (Min~Max)		PK	1.5	2	2.5
		Btu/h	11,900 (4,400 ~ 13,000)	17,100 (4,800 ~ 18,400)	20,500 (5,800 ~ 20,500)
		kW	3.50 (1.3 ~ 3.8)	5.0 (1.4 ~ 5.4)	6.0 (1.7 ~ 6.0)
Daya Listrik (Min~Max)		W	1,200 (250 ~ 1,460)	1,730 (355 ~ 2,070)	2,210 (370 ~ 2,510)
COP (Min~Max)		W/W	2.92	2.89	2.71
Tingkat Tekanan Suara (H/L/SL)		Indoor	37/28/24	44/35/29	45/37/31
		Outdoor	49	51	52
Indoor Unit	Dimensi (HxWxD)	mm	285 × 770 × 223	285 × 770 × 223	285 × 770 × 223
	Berat Mesin	kg	8	8	8
Outdoor	Dimensi (HxWxD)	mm	550 x 658 x 275	595 x 845 x 300	595 x 845 x 300
	Berat Mesin	kg	26	36	40
Ukuran Pipa		Cair	inch	1/4	1/4
		Gas	inch	3/8	1/2
Maksimal Pipa		Panjang	m	15	30
		Tinggi	m	12	20